JN884 Workwear Softshell Jacket - SOLID -







Professional, light softshell jacket in 'classic' look with highquality details

Durable, hard-wearing softshell, inside fleece

Wind- and water-repellent (2,000 mm water column)

Breathable and permeable to water vapour (2,000g/m²/24h

Stand-up collar

Ergonomically shaped sleeves, extended back

Inner sleeve cuffs

Full-length concealed zip with storm flap and chin cup

Zipped side pockets and inner pocket

Breast pockets with pocket pouch sewn on only on one side to facilitate decoration

Several inner pockets

Reflective elements (without protective function / no PPE) on pockets, sleeves, shoulders and at the back

Zips: YKK

Buttons and zips:

In order to avoid the product in hand being damaged, all the buttons and zips are concealed.

Fabric: Outer fabric (320 g/m²): 100%

polyester

Country of origin: China

Customs tariff number 62113310

Care instructions




Available colours

	xs	S	М	L	XL	XXL	3XL	4XL	5XL	6XL
Weight in g	759g	799g	830g	851g	897g	921g	978g	1002g	1104g	1201g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/20	1/20	1/20	1/20	1/20	1/20	1/20	1/20	1/20	1/20
measurem	xs	S	М	L	XL	XXL	3XL	4XL	5XL	6XL
ents in cm										
1/2 chest:	52,00 cm	55,00 cm	58,00 cm	61,00 cm	64,00 cm	67,00 cm	70,00 cm	74,00 cm	78,00 cm	82,00 cm
front	70,00 cm	71,00 cm	72,00 cm	74,00 cm	76,00 cm	78,00 cm	80,00 cm	82,00 cm	84,00 cm	86,00 cm
length										
from										
shoulder:										
length	74,00 cm	75,00 cm	76,00 cm	78,00 cm	80,00 cm	82,00 cm	84,00 cm	86,00 cm	88,00 cm	90,00 cm
back from										
shoulder:										
sleeve	64,00 cm	65,00 cm	66,00 cm	67,00 cm	68,00 cm	69,00 cm	70,00 cm	71,00 cm	72,00 cm	0,00 cm
length:										

Available colours











Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.

Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 10.12.2019 - 14:39:10